

FreqCheck™

FREQUENCY AUDIT REPORT | IND CORE™ TECHNOLOGY

REPORT ID: 6A9AC6EA-8DE60618-92259E
TIMESTAMP: 4.9.2026, 15:26
SOURCE CATEGORY: Line In (Instrumentation)
ANALYSIS MODE: LIVE SOURCE

METROLOGY CONFIGURATION SNAPSHOT


WIDEBAND METROLOGY: ACTIVE
SAMPLE RATE: 48.0 kHz
SENSITIVITY: 1.02 mV/Pa
CHANNEL: LEFT
ADC CEILING: 10.00 V
OFFSET: +0.0 dB
MAX AMPLITUDE: 140.6 dB

LABORATORY SPECTRAL TELEMETRY

UNCERTAINTY DISCLOSURE: NIST-Traceable Adaptive Quantization Limits ± 0.146 Hz to ± 0.73 Hz.
Reported values reflect Dynamic FFT Bin Centers based on band-specific frequency resolution @ 48.0kHz.

ANALYSIS MODE	SPECTRUM BOUNDARIES	MAX AMPLITUDE	WIDEBAND PEAK
TACTICAL WIDEBAND	30.0 Hz - 24.0 kHz	140.6 dB	433.59 Hz

FORENSIC SPECTRAL TRACE (PEAK HOLD)



LICENSE RESTRICTION: Valid for Technical Verification & Media Analysis. Void if used for Commercial Manufacturer Certification or Packaging Claims.

CRYPTOGRAPHIC SEAL (SHA-256): fba35fe98ba480baafa46e918034c9254f09d6036def5ec864dae712e04a7a6f

Copyright © 2025-2026 Abundance Sea, LLC. All Rights Reserved. U.S. Patent No. 12,659,418; Patent Pending 19/660,467.
IND CORE™ Technology is ISO 17025:2017 Calibrated (Cert #05122C9A 2602).

DETECTION CHRONOLOGY (TIMECODE BREAKDOWN)

TIME	BAND	SIGNAL	INTENSITY
15:22:06.50	SIGNAL	433.59 Hz	125.1 dB